



General specifications

- Mounting without screws in square openings as indicated in the cut-out diagram
- Plate thickness between 1.5 and 2.2mm
- Plastic parts in PC/ABS alloy
- Permanent sealing gasket in polyurethane foam
- Filter media in thermo-linked progressive structure synthetic fibre
- filter class G3 (optionally filter class G4), according to EN 779
- Filter media can be cleaned, up to 10 times by washing, blowing dry and lightly beating
- IP55, Type1, 3R and EMC versions on request
- UL approval according to UL 508



- ▶ Electromagnetic radiation protection
- ▶ Clip mounting system
- ▶ Low profile

Technical data

Model	A	B	C	D	E	F	G	Weight	Approvals
	mm	mm	mm	mm	mm	mm	mm	Kg	
FPF12KUGC-110	150	124	21	7	131	125	4.5	0.24	CE;
FPF13KUGC-110	204	175	20	8	185	177	4.5	0.34	CE;
FPF15KRGC-110	250	220	23	8	230	223	4.5	0.61	CE;
FPF15KUGC-110	250	220	23	8	230	223	4.5	0.61	CE;
FPF20KRGC-110	325	288	24	9	302	291	4.5	1	CE;
FPF20KUGC-110	325	288	24	9	302	291	4.5	0.98	CE;

Technical specifications

