

Identification	Type	LOCC-Box-BKR 7-6429
	Part-No.	716429
Technical data		
Number of terminations	8-pole	
Input		
Rated current	6 A	
General		
Number of terminations	8-pole	
Rated current	6 A	
Contact type	Strength: 0.5 mm; smooth	
Pin spacing	8.2 mm	
Contact material	FeZn	
Housing material	PVC hard	
Color	red	
Class of flammability according to UL 94	V0	
Operation temperature range	-40 °C – 80 °C	
Storage temperature range	-40 °C – 80 °C	
Dimensions (w x h x d)	22.5 x x mm	
Weight (kg/piece)	0.003	
Termination	plug-in	

11.11.2014 – Subject to technical modification

Part-No. 716429

USA: LUTZE INC.


13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



Dimensions



11.11.2014 – Subject to technical modification

Part-No. 716429

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA

Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223

www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park

Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU

Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2

www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY